

Remove Watermark Now

## Dayton® Hand Dryers



■ UL, C-UL, CSA, and CE certified

### HIGH-SPEED

Energy efficient, antimicrobial units feature 10-sec. dry time with 2-3 times longer service life than traditional units. On/Off heating and 3 speed motor controls that optimize energy efficiency. GreenSpec listed for LEED points.

### HIGH SPEED VERTICAL

High-speed, antimicrobial, "hands-in" dryer is ADA-compliant and is activated by an infrared sensor. LED indicates when to empty the water collection reservoir and when to inspect the HEPA filter for replacement. Includes 6-ft. polarized cord for direct connection to polarized outlet.

### INDUSTRIAL

Porcelain enamel finish won't break, dent, or scratch.

### UNIVERSAL HIGH-SPEED ADA

Dryers are antimicrobial and ADA-compliant with universal voltage, 15-sec. drying time, and uses 70% less energy. Ultra compact unit includes On/Off heating controls. GreenSpec listed for LEED points.

### INDUSTRIAL HIGH OUTPUT

50% reduced dry-time. Nozzle can be converted to rotate. Dryers can contribute to LEED points for energy efficiency.

### COMMERCIAL LOW PROFILE

Protrudes only 4" from wall for ADA compliance for No. 38U95 only.

### COMMERCIAL LOW NOISE

Triple-plated, brushed chrome finish hides smudges and fingerprints. No. 1GVL9 has a 1/10 HP shaded pole brushless motor.



No. 6PGK6      No. 19UC76

Nozzle Type	Finish	Cover	Activator	Dry Time	Voltage	Amps	Item No.
<b>High Speed</b>							
Integral	Chrome - Polished	Aluminum	Automatic	10 sec.	115	10	6PGK6 ✓
Integral	Brushed Stainless Steel	Stainless Steel	Automatic	10 sec.	115	10	6PGK8 ✓
Integral	White Epoxy	Aluminum	Automatic	10 sec.	115	10	6PGK9 ✓
Integral	White Epoxy	Cast Aluminum	Automatic	12 sec.	115	9.6	3NXE5 ✓
<b>High Speed Vertical</b>							
Fixed	Paint	ABS Plastic	Automatic	12 sec.	115	10	19UC76 ✓
<b>Industrial</b>							
Swivel	Porcelain Enamel	Cast Iron	Push Button	30 sec.	115	20	5W630 ✓
Fixed	Porcelain Enamel	Cast Iron	Automatic	30 sec.	115	20	6H009 ✓
<b>Universal High-Speed-ADA Surface Mounted</b>							
Fixed	Polished Chrome	Cast Aluminum	Automatic	15 sec.	115, 200, 230	8.3/3.7/4.1	22UZ65 ✓
Fixed	Brushed Chrome	Cast Aluminum	Automatic	15 sec.	115, 200, 230	8.3/3.7/4.1	22UZ66 ✓
Fixed	Stainless Steel	Cast Aluminum	Automatic	15 sec.	115, 200, 230	8.3/3.7/4.1	22UZ67 ✓
Fixed	White Epoxy	Cast Aluminum	Automatic	15 sec.	115, 200, 230	8.3/3.7/4.1	22UZ68 ✓
<b>Industrial High Output</b>							
Swivel	Porcelain Enamel	Cast Iron	Push Button	15 sec.	115	20	4ZA64 ✓
Fixed	Porcelain Enamel	Steel	Automatic	15 sec.	115	20	3NXE9 ✓
<b>Commercial Low Profile</b>							
Fixed	White Epoxy	Cast Aluminum	Automatic	30 sec.	115, 200, 230	8/7/6	3BU95 ✓
Fixed	White Epoxy	Steel	Automatic	25 sec.	115, 200, 230	15/10/8.7	3BU99 ✓
Fixed	White Epoxy	Cast Aluminum	Automatic	30 sec.	115	8	1GVL8 ✓
<b>Commercial Low Noise</b>							
Fixed	Brushed Chrome	Cast Aluminum	Automatic	30 sec.	115	17	6H010 ✓
Fixed	Epoxy Enamel	Cast Aluminum	Automatic	30 sec.	115	15	1GVL9 ✓



## XLERATOR® Hand Dryers

■ UL, C-UL, and CE certified

Dries hands 3 times faster and uses 80% less energy. Dryers are GreenSpec listed and can contribute to LEED points for energy efficiency. No. 2KJJ8 features a vandal-resistant cover. Nos. 2KJJ9 and 2KJK1 have a chip-resistant epoxy cover. No. 3PDE6 is a noise-reducing nozzle. No. 3DYH4 converts XLERATOR® dryers to be ADA compliant.

Nozzle Type	Finish	Cover	Activator	Dry Time	Voltage	Amps	Item No.
<b>Dryers</b>							
Fixed	BMC	BMC	Automatic	10 sec.	115	12.5	2KJJ8 ✓
Fixed	White Powder Coated	Zinc Diecast	Automatic	10 sec.	115	12.5	2KJJ9 ✓
Fixed	Textured Graphite	Zinc Diecast	Automatic	10 sec.	115	12.5	2KJK1 ✓
Fixed	Brushed Stainless Steel	Steel	Automatic	10 sec.	115	12.5	3DYH3 ✓

Accessories	Nozzle Type	Finish	Item No.
Noise-Reducing Nozzle			3PDE6
ADA Recess Kit	Stainless Steel		3DYH4 ✓

No. 20RX04

dyson

## Dyson Airblade™ Hand Dryers

■ 110 to 127V  
■ Meet NSF P335 standards

Modern-design dryers provide an extremely fast and hygienic way to dry hands. Engineered to fit a variety of restroom environments. Nos. 20RX06, 20RX07 and 20RX08 are tap-operated combination units that allow you to wash and dry hands at the sink.



No. 20RX10

Description	Finish	Color	Activator	Item No.
<b>Hand Dryers - 12 Sec. Dry Time</b>				
Low-Noise Dryer	Antimicrobial	Gray	Infrared Sensor	20RX04 ✓
Low-Noise Dryer	Antimicrobial	White	Infrared Sensor	20RX05 ✓
Compact Dryer	Antimicrobial	Silver	Sensor/Capacitive	20RX09 ✓
Compact Dryer	Antimicrobial	White	Sensor/Capacitive	20RX10 ✓
<b>Sink Tap w/ Hand Dryer - 14 Sec. Dry Time</b>				
Tap Operated Dryer w/ Mounting Hardware	Stainless Steel	Silver	Infrared Sensor	20RX08 ✓
Tap Operated Dryer w/ Short Tap Mounting Hardware	Stainless Steel	Silver	Infrared Sensor	20RX06 ✓
Tap Operated Dryer w/ Long Tap Mounting Hardware	Stainless Steel	Silver	Infrared Sensor	20RX07 ✓



## Medicine Cabinets and Mirrors

H (in.)	W (in.)	D (in.)	Item No.
<b>Recessed Medicine Cabinets - Polystyrene</b>			
22	16	4½	6MX Y8
<b>Recessed Medicine Cabinets - Painted White Enamel Steel, 26 Ga.</b>			
22	16	4½	6MX Y2
26	16	4½	6MX Y3
36	16	5	6MX Z0

H (in.)	W (in.)	D (in.)	Item No.
<b>Surface Mount Medicine Cabinets - Painted White Enamel Steel, 26 Ga.</b>			
22	16	5	6MX Y4
26	16	5	6MX Z1
<b>Lockable Medicine Cabinets - Satin Stainless Steel, 22 Ga.</b>			
9¾	15¾	4¾	6MX Z9
<b>Surface Mount Medicine Cabinets - Painted White Enamel Steel, 22 Ga.</b>			
19¾	24	8½	6MX Y9

H (in.)	W (in.)	D (in.)	Item No.
<b>Round Corner Surface Mount, Right Hand Medicine Cabinets - Painted White Enamel Steel, 20 Ga.</b>			
22	16	4	6MX Z2
<b>Fixed Tilt ADA Compliant Mirrors - Stainless Steel</b>			
30	16	4	19UC66
36	18	4	19UC67
36	24	4	19UC68
<b>Adjustable Tilt ADA Compliant Mirrors - Stainless Steel</b>			
30	16	1	19UC69
36	18	1	19UC70
36	24	1	19UC71
<b>Washroom Mirrors - Galvanized Sheet Steel</b>			
22	16	½	6MX Y5
24	18	½	6MX Y6
30	18	½	6MX Y7



No. 6MX Y5

H (in.)	W (in.)	D (in.)	Item No.
<b>Shatterproof Safety Mirrors - Stainless Steel 22 Ga.</b>			
20	16	1/6	6MX Z6

Remove Watermark Now



No. 3PCH5



No. 4ACU5

No. 2VHR5



**Healthcare Supplies**

**Maternity Pads**—Nonwoven cover stock with absorbent core. Individually wrapped, with adhesive for secure attachment.

**Wash Cloths and Towels**—No. 3PCH5 features cloth-like material and perforated overwrap. No. 3PCJ1 can be heated in microwave or under tap water for rinse-free bathing. Provide an alternative to fresh linens at shower/safety stations. Airlaid, bonded cellulose has high capacity, absorbency, and durability. Individually poly-wrapped to protect from contamination and moisture. Multipurpose, absorbent wipers help reduce the cost and inconvenience of laundering and pilferage. Natural rubber and latex-free.

Type	Size	Brand	Item No.	Pkg. Qty.
<b>All Night OB Maxi Pads</b>				
All Night Coverage	2½" x 12"	Hospesco	3PCJ2	288
<b>Overnight Maxi Pads</b>				
Overnight Coverage	2½" x 12"	Hospesco	3PCJ3	168
<b>Wash Cloths &amp; Towels</b>				
Dry Wash Cloth	10" x 13"	Hospesco	3PCH5	500
Disposable Wipes	11½" x 12½"	Tough Guy	39M981	1080
Personal Bath Towel	20 x 39"	Georgia-Pacific	6RA68	1
Washcloths	12½" x 13"	Georgia-Pacific	4ACU5	18
Premium Wash Cloths	12½" x 13"	Georgia-Pacific	4CJ98	20
X50 Hygienic Washcloth	10" x 12½"	Kimberly-Clark	2VHR5	832
X60 Hygienic Washcloth	10" x 12½"	Kimberly-Clark	2VHR6	560
L40 Dry-Up Towel	19½" x 42"	Kimberly-Clark	2XRN2	200
X60 Shower Towel	20" x 43¾"	Kimberly-Clark	2VHR3	300

**Toilet Seat Covers, Door Tissues, and Dispensers**

**TOILET SEAT COVERS**

Biodegradable seat covers provide a hygienic barrier for sanitary protection.

**PLASTIC DISPENSERS**

Hold 500 ½-fold or 200 ¼-fold seat covers.

**¼-Fold**—12"H x 8½"W x 2½"D.

**½-Fold**—11½"H x 16¼"W x 2½"D.

**STAINLESS STEEL DISPENSER**

Satin finish; holds 250 single-fold or ½-fold seat covers. 11"H x 15¾"W x 2"D.



No. 2VEX7

No. 22LC68


**CHROME-PLATED STEEL DISPENSER**

Holds 250 seat covers. 11½"H x 16¾"W x 1¾"D.

**DOOR TISSUE AND DISPENSER**

Mount Safe-T-Gard® dispensers next to washroom exit doors and use tissues as a barrier between hands and door handles. Dispensers are 6¾"W x 11"H x 4"D.

Description	Color	Item No.	Pkg. Qty.
<b>Tough Guy® Disposable Toilet Seat Covers</b>			
¼ Fold, Paper	White	2VEX5	25
½ Fold, Paper	White	2VEX6	20
<b>Tough Guy® Toilet Seat Cover Dispensers</b>			
Plastic for ¼ Fold	White	2VEX7	1
Plastic for ½ Fold	White	2VEX8	1
Plastic for ½ Fold	Gray	2VEX9	1
Polypropylene for ½ Fold	Smoke	22LC68	1
304 22 Gauge Stainless Steel	Satin	1ECK2	1
Chrome-Plated	Chrome	3P916	1
<b>Georgia-Pacific Safe-T-Gard® Door System</b>			
Tissue, Door Handle	White	1LYJ3	40
Dispenser and Receptacle	Splash Blue	1LYH8	1
Door Tissue Dispenser	Splash Blue	1LYH9	1
Dispenser and Receptacle	Smoke	J1310	1
Door Tissue Dispenser	Smoke	J1311	1



No. 2NXW2



No. 4RCZ4

**Feminine Hygiene Receptacles & Liners**

**RECEPTACLES**

**Polypropylene Wall-Mounted Receptacle**—Receptacle has a lightweight, easy-to-lift lid.

**Metal Floor Receptacle**—Unit fits under the stall and has a swing door allowing access from 2 stalls.

**Stainless Steel Wall-Mounted Receptacle**—Stainless steel satin finish. Hinged lid.

**POLYETHYLENE LINER**

Bottom seal for leakproof usage and spill prevention when removing liner. Black color prevents viewing of internal contents.

Description	L	W	H	Item No.	Pkg. Qty.
<b>Receptacles</b>					
Polypropylene Wall-Mounted Receptacle	12"	5¼"	10"	2NXW1	1
Metal Floor Receptacle	9¾"	9"	11½"	2NXW2	1
304 Stainless Steel Sanitary Napkin Receptacle	9¼"	4¼"	11"	1ECK9	1
<b>Liners</b>					
Polyethylene Sanitary Napkin Bin Liner	17"	17"	17"	4RCZ4	1000



**Feminine Hygiene Supplies**

**TAMPONS AND SANITARY NAPKINS**

**Regular Tampax® Tampons**—100% cotton and/or rayon blend, biodegradable, and flushable. (Outer tube not flushable.)

**Maxithins® #4 and #8 Maxi Pads**—Individually boxed.

**Maxithins® Gards® Ultra-Thin Pads with Wings**—Individually boxed in #4 carton.

**DISPENSERS**

**Dual Vendor**—Dispenses 15 No. 3U818 or 4HJ66 pads and 25 No. 3U822 tampons. White color. No. 3U821 dispenser has \$0.25 coin release, No. 40L817 is coin-free.

**Stainless Steel Vendor**—Dispenses 15 No. 3U818 or 4HJ66 pads and 25 No. 3U822 tampons. \$0.25 coin release. Made of 18-gauge, 304 stainless steel.

No. 3U821

**KITS**

**Convenience Pak**

Kit contains white dual junior dispenser and No. 3U820 starter kit with pads, tampons, and disposal bags. Dispenses 9 pads and 13 tampons. \$0.25 coin release.

**Starter Kit**—Contains 60 Maxithins® pads, 60 Tampax® tampons, and 60 Necessities disposal bags.

**KRAFT WAXED PAPER LINERS**

Use No. 3U825 with standard swing door napkin receptacle. Use No. 3U824 with No. 2NXW1 receptacle and all standard sanitary napkin receptacles. No. 5FW85 liner with gussets fits Sanisac and No. 2NXW1 receptacles.

**NECESSITIES COURTESY BAGS**

Printed white bag mounts directly on vendor.



Description	L	W	H	Item No.	Pkg. Qty.
<b>Tampons and Sanitary Napkins</b>					
Regular Tampax® Tampons	5"	¾"	¾"	3U822	500
Maxithins® #4 Maxi Pads	4¼"	3¼"	1"	3U818	250
Maxithins® #8 Maxi Pads	8"	3¼"	1"	3U819	250
Maxithins® Gards® #4 Ultra-Thin Pads	4¼"	3¼"	1"	4HJ66	200
<b>Dispensers</b>					
Dual Vendor, 25 Cent Machine	10"	6¾"	26¼"	3U821	1 ✓
Dual Vendor, Coin-Free	10"	6¾"	26¼"	40L817	1 ✓
Stainless Steel Vendor	10"	6¾"	26¼"	4HJ63	1 ✓
<b>Kits</b>					
Convenience Pak	6¼"	10¾"	17"	3U823	1
Starter Kit	4¼"	3¼"	1"	3U820	1
<b>Liners</b>					
Kraft Waxed Paper Sanitary Napkin Bags	8"	8"	7"	3U825	500
Kraft Waxed Paper Sanitary Napkin Bags	9"	3¼"	10"	3U824	250
Kraft Sanitary Napkin Bag With Gusset	3½"	7½"	10¼"	5FW85	500
Necessities Courtesy Sanitary Napkin Bag	8"	3"	2"	5FW86	500

Remove Watermark Now

### 3M™ Clean-Trace™ Hygiene Management System

Detects the presence of organic contamination not visible to the human eye. Allows users to quickly measure surface cleanliness, validate the efficacy of cleaning protocols, and track data for analysis. The lightweight, portable luminometer provides a reading in under 30 seconds. Suitable for use in hospitals, clinics, surgical centers, and nursing facilities.



Description	No. of Stored Sample Plans	Model	Part No.	Quantity
3M™ Clean-Trace™ NGI Luminometer	45	NGI	5UXE8	1
ATP Surface Swabs	—	UXL100	5UXE9	100
Luminometer Docking Station	—	NSTATION	5UXF0	1
Luminometer Battery	—	NGLBP1	5UXF1	1
Luminometer Soft Carry Case	—	NSGSB1	5UXF2	1



No. 5UXE8

### Baby Changing Table and Baby Seat

**Baby Changing Stations**—Wall-mounted stations with concave surface. Include replaceable nylon safety straps, bag/purse hooks, mounting hardware, and a built-in sanitary liner dispenser. Stations meet or exceed ADA, ASTM, and ANSI requirements.

**Baby Seat**—Unit fits inside fitting room or restroom stall without compromising space. Seat has molded-in bag hook, Y-harness safety belt, a concave bed, and head and side support.



No. 6PXW4



No. 1MDU8

Description	L (in.)	W (in.)	Mr. Model	Item No.
<b>Polyethylene Baby Changing Station by Koala Kare Products</b>				
Vertical	35½	22	KB101-00	2ELE6
<b>Polypropylene Baby Changing Station by Koala Kare Products</b>				
Horizontal	22	35	KB200-00	6PXW4
<b>Stainless Steel Baby Changing Station by Koala Kare Products</b>				
Horizontal	35¼	20	KB110-SSWM	2ELE7
<b>Changing Station Liners for Baby Changing Stations by Koala Kare Products</b>				
3-Ply Biodegradable Paper Liners, Pkg. of	19	13	KB150-99	2ELZ8
<b>Plastic Baby Wall Seat by Hospeco</b>				
150-lb. Capacity	22¼	13¼	67018	1MDU8

Description	For Use With	Mr. Model	Item No.
<b>Replacement Parts for Koala Kare Baby Changing Stations</b>			
Baby Changing Station Strap	2ELE5, 2ELE7	885	2ERH4
Baby Changing Station Strap	2ELE6	889	2ERH5
Baby Changing Station Shock	2ELE5, 2ELE7	874	2ERH6
Baby Changing Station Shock	2ELE6	877	2ERH7
Baby Changing Station Shock	2ELE7	875	2ERH8
Baby Changing Station Front Label	2ELE5, 2ELE6, 2ELE7	825	2ERH9

### Access Doors

Conceal wall openings with a secure cover that can be finished to match wall color.



#### STANDARD

**Steel**—16-ga. steel door with paintable powder coat primer. Flush-mount doors with pin hinge (continuous piano hinge for Nos. 2VEE7 and 2VEE8). Screwdriver-operated cam latch.

**Stainless Steel**—Corrosion-resistant door and frame.

#### MEDIUM SECURITY

14-ga. steel with baked-on paintable prime coat. Continuous piano hinge and key-operated cylinder lock.

#### ADJUSTABLE

20-ga. steel door with 24-ga. steel frame with notched knock over tabs and 4 polymer corners with embedded magnets. Quick installation with minimal tools and no framing required. Adjustable by 1½" in height and width. Magnetic latching mechanism. Paintable prime coat.

#### HIDDEN FLANGE

16-ga. exclusive steel door with flange hidden behind beveled door panel. Flush mount with european-type hinge. Screwdriver-operated cam latch. Paintable powder coat primer.

Door Dim.		Rough Opening		Item No.
W	H	W	H	
<b>Standard, Steel</b>				
8"	8"	8¼"	8¼"	5YL92
10"	10"	10¼"	10¼"	5YL93
12"	12"	12¼"	12¼"	5YL94
12"	12"	12¼"	12¼"	1UEW7 *
14"	14"	14¼"	14¼"	5YL95
14"	14"	14¼"	14¼"	1UEW8 *
16"	16"	16¼"	16¼"	5YL96
16"	16"	16¼"	16¼"	1UEW9 *
18"	18"	18¼"	18¼"	2VEE5
18"	18"	18¼"	18¼"	16M208 *
16"	24"	16¼"	24¼"	2VEE4
18"	24"	18¼"	24¼"	2VEE6
24"	24"	24¼"	24¼"	5YL97
24"	24"	24¼"	24¼"	1UEX1 *
24"	36"	24¼"	36¼"	2VEE7
36"	36"	36¼"	36¼"	2VEE8
<b>Standard, Stainless Steel</b>				
10"	10"	10¼"	10¼"	2VEE2
16"	16"	16¼"	16¼"	2VEE3
<b>Medium Security, Flush</b>				
12"	12"	12¼"	12¼"	1UEV7
16"	16"	16¼"	16¼"	1UEV8
18"	18"	18¼"	18¼"	1UEV9
24"	24"	24¼"	24¼"	1UEX2

\* Includes cylinder lock and key.

#### ACOUSTICAL, FOR DRYWALL

16-ga. steel door with paintable primer coat. Continuous piano hinge. Allen hex head operated cam latch. 5/8" recessed door panel.

#### DRYWALL

16-ga. door and frame with drywall corner bead flange. Flush mounted with concealed pin hinge. Screwdriver operated cam latch. Paintable prime coat.

#### INSULATED, ALUMINUM

16-ga., corrosion-resistant aluminum door and frame. Feature 1"-thick insulation and gasket around perimeter. Key operated cylinder lock. Continuous piano hinge. Paintable powder coat primer.

#### FIRE-RATED, INSULATED, STANDARD

16-ga. steel frame and 20-ga. steel door with automatic panel closer and inside release. Self latching tool or ring operated slam latch. 2" mineral wool insulation for a 2-hr. fire barrier and 1½-hr., B label. Fire rating of 1½ hr. in walls, 3 hr. in noncombustible ceilings and 1 hr. in combustible ceilings. Paintable powder coat primer.

**Upward-Swinging**—For ceilings only. Same as fire rated insulated model but the panel swings up and shuts down by way of gravity instead of springs. The continuous piano hinge keeps the panel from opening more than 87°. Self-latching, ring operated slam latch (inside) allen hex head (outside).

Door Dim.		Rough Opening		Item No.
W	H	W	H	
<b>Adjustable</b>				
6" to 7½"	6" to 7½"	6" to 7½"	6" to 7½"	20TL30
8" to 9½"	8" to 9½"	8" to 9½"	8" to 9½"	20TL31
10" to 11½"	10" to 11½"	10" to 11½"	10" to 11½"	20TL32
12" to 13½"	12" to 13½"	12" to 13½"	12" to 13½"	20TL33
14" to 15½"	14" to 15½"	14" to 15½"	14" to 15½"	20TL34
6" to 7½"	6" to 7½"	6" to 7½"	6" to 7½"	20TL35
8" to 9½"	8" to 9½"	8" to 9½"	8" to 9½"	20TL36
10" to 11½"	10" to 11½"	10" to 11½"	10" to 11½"	20TL37
12" to 13½"	12" to 13½"	12" to 13½"	12" to 13½"	20TL38
14" to 15½"	14" to 15½"	14" to 15½"	14" to 15½"	20TL39
<b>Hidden Flange</b>				
8¼"	8¼"	8½"	8½"	16M209
12"	12"	12¼"	12¼"	16M210
14"	14"	14¼"	14¼"	16M211
16"	16"	16¼"	16¼"	16M212
18"	18"	18¼"	18¼"	16M213
24"	24"	24¼"	24¼"	16M214
<b>Acoustical For Drywall</b>				
8"	8"	8¼"	8¼"	16M220
12"	12"	12¼"	12¼"	16M221
24"	24"	24¼"	24¼"	16M222



Standard, Steel No. 1UEX1

Drywall No. 2VEE2

Plastic No. 5YM02

#### FIRE-RATED, UNINSULATED, STANDARD

16-ga. steel door for vertical fire-rated surface only where temperature rise protection is not required. Self-latching tool or ring operated slam latch with inside release. Automatic panel closer. Fire rating of 1½ hr. B-Label for 2-hr. rated walls. Paintable powder coat primer.

#### PLASTIC

High-impact, noncorrosive ABS plastic doors are UV stabilized for exterior use. Patented reversible frame for surface or flush mounting. Can be painted, wallpapered, or tiled. Surface-mount doors are removable with a screwdriver. No. 5YM02 has punch-outs for electric and plumbing.

Door Dim.		Rough Opening		Item No.
W	H	W	H	
<b>Drywall</b>				
8"	8"	8¼"	8¼"	2VE75
12"	12"	12¼"	12¼"	2VE72
16"	16"	16¼"	16¼"	16M207
18"	18"	18¼"	18¼"	2VE73
24"	24"	24¼"	24¼"	2VE74
<b>Insulated, Aluminum</b>				
8"	8"	8¼"	8¼"	2VEE9
12"	12"	12¼"	12¼"	2VEE0
16"	16"	16¼"	16¼"	2VEE1
18"	18"	18¼"	18¼"	2VEE2
24"	24"	24¼"	24¼"	2VEE3
36"	36"	36¼"	36¼"	2VEE4
<b>Fire-Rated, Insulated, Standard</b>				
8"	8"	8¼"	8¼"	16M205
12"	12"	12¼"	12¼"	5YL98
16"	16"	16¼"	16¼"	5YL99
18"	18"	18¼"	18¼"	2VE76
22"	30"	22¼"	30¼"	5YM01
22"	36"	22¼"	36¼"	2VE77
24"	24"	24¼"	24¼"	16M206
<b>Fire-Rated, Insulated, Upward-Swinging</b>				
24"	24"	24¼"	24¼"	2VE80
22"	30"	22¼"	30¼"	2VE78
22"	36"	22¼"	36¼"	2VE79
<b>Fire-Rated, Uninsulated, Standard</b>				
8"	8"	8¼"	8¼"	16M215
12"	12"	12¼"	12¼"	16M216
16"	16"	16¼"	16¼"	16M217
18"	18"	18¼"	18¼"	16M218
24"	24"	24¼"	24¼"	16M219
<b>Plastic</b>				
6"	9"	6¾"	9¾"	5YM02
13¾"	13¾"	14"	14"	5YM03
13¾"	29"	14"	29½"	2VE81